



TERMINALES ROBA CORRIENTE AISLADAS




CLAVE	A.W.G mm ²	Dimensiones (mm)	
		W	L
TRR	22-18 0.5-1.0 mm ²	20.0	27.0
TRA	16-14 0.75-2.5 mm ²	20.0	27.0
TRAM	12-10 4-6 mm ²	20.5	34.5

CAPUCHÓN AISLANTE PARA UNIR CABLES



CLAVE	A.W.G	Dimensiones (mm)		
		L	B	C
CRG	22-16	8.5	3.5	14.7
CRA	22-14	10.1	6.5	17.5
CRN	22-14	11.2	8.0	21.4
CRAM	18-12	13.7	7.5	23.6
CRR	18-10	16.0	7.0	26.5

CAPUCHÓN AISLANTE DE PRESIÓN



CLAVE	W (mm)		D (mm)	Cables Compatibles	
	B	C		mm ²	A.W.G
CB2	8.2	4.0	2.9	2.0	16-14

PRENSA MANUAL DE GOLPE



CLAVE	Prensa de golpe para:	
	Terminales	A.W.G
19-PT	Cobre estañado A tope de cobre estañado	2, 4, 6, 8, 0/1, 0/2, 0/3, 0/4 2, 4, 6, 8, 0/1, 0/2, 0/3, 0/4